# ATS1455

## (10 stk) Mifare Desfire EV2 firkantet proxkort

### Product overview

The ISO card in white color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV2 encryption. It can be used in secure mode with ATS118x range readers and ATS1136 keypad.
When used on other Mifare Readers the standard Mifare 7-byte CSN is provided instead of the secure card data.




### Detaljer

- Attractive designed keyfob in ISO card model
- Card data secured by AES encryption
- Mifare Desfire EV2 encrypted application

# ATS1455

## (10 stk) Mifare Desfire EV2 firkantet proxkort

## Tekniske specifikationer

### System

| | |
|---|---|
| Reading distance | Secure mode: between 1 - 5 cm<br>Unsecure mode: between 2-5 cm<br>Distance may vary based on reader |
| Custom data model | No |
| Memory size | 2 kB |
| Supported readers | ATS ATS118x Secure Readers |

### Technology

| | |
|---|---|
| Credential type | Smart kort |
| Credential operating frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN) |

### Printing

| | |
|---|---|
| Direct surface printing | No |

### Ordering information

| | |
|---|---|
| Minimum order quantity | 1 |
| Cards/tags in package | 10 |

### Physical

| | |
|---|---|
| Material | PVC |
| Form factor | Klemmeskal |
| Physical dimensions | 86 x 54 x 9 mm |
| Net weight | 66 g |
| Shipping weight | 67 |
| Colour | Hvid |
| Card Label | Serial number |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +50°C |
| IP rating | IP68 |

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57