ATS1140

Touchscreen 7" per Everon e Advisor Advanced

At a glance

The Advisor Advance product family has a new addition - the ATS1140 graphical touchscreen. This device offers simple fingertip control of the security system with a 7-inch high-responsive touchscreen display that features easy-to-understand graphics. The ATS1140 is designed to perfectly complement other control units in the Advisor Advance security system family, ensuring a smooth user experience.

The ATS1140 boasts a modern design with a new graphical user interface that features icon-based and readable text. The display's contrast and the built-in buzzer's volume level can be adjusted via the configuration board. This device also comes with a simplified and intuitive graphical user interface, allowing users to easily navigate the programming, operational features, dashboard, system status, alarms, logs, and additional function keys.

Overall, the ATS1140 graphical touchscreen combines functionality and style to provide an efficient and user-friendly experience.



Built-in secure card reader

The ATS1140 is equipped with a Mifare Desfire EV1/EV2/EV3 card reader that is built-in. When the device is in secure mode, the card data is transferred in a safe and encrypted manner from the card to the keypad and from the keypad to the Advisor Advance control panel.

The ATS1140 can be utilized for arming/disarming the system using either the PIN or the card, or a combination of both for enhanced security. It is suitable for multiple card badging techniques that are available for the Advisor Advance product family. For instance, a user can badge their card three times within 10-second intervals to set the system in the evenings. Another application could be for doors that can be programmed to unlock when badged once, allowing people to enter and exit without a card. The door can be re-locked by badging thrice, all for the end user's convenience.

Quick Access

The touch display menus are thoughtfully organized, featuring a clean and intuitive design that makes navigation a breeze. The single-touch operation eliminates the need for complex manoeuvres, allowing for effortless interaction with the system. Whether you are an advanced tech user or a novice, you will find the touch display menus to be user-friendly and highly accessible.

Installation

Quick and easy installation.
Just screw the back plate onto the wall using four screws, don't forget the screw for the tamper.
Next, connect the data bus cable from the panel; once done, simply snap the touchscreen onto the plate, and voila!
You're all set up and ready to go.

Dettagli

- Design moderno
- Interfaccia utente grafica semplificata ed intuitiva
- Touchscreen 7" a colori
- Logo personalizzato
- Tasti funzione programmabili rapidamente accessibili
- Lettore Mifare Desfire EV1/EV2/EV3 integrato
- LCD, cicalino e luminosità regolabili dall'utente
- Compatibile con le tessere della serie ATS145x (escl. ATS1458)
- Supporto multi-lingua
- Tastiera virtuale

This installation method is not only easy to follow, but it also ensures a secure fit for your touch screen, providing you with peace of mind knowing that your device won't fall off the wall.
In order to connect the Advisor Advance security system to ATS1140, the panel must have MR4.10 or later. Please contact your local support for assistance if needed.

ATS1140

Touchscreen 7" per Everon e Advisor Advanced

Specifiche tecniche

General

User interface	Touches réactives Surface Keys
Product line	Advisor Advanced, Everon
Status LEDs	12
Integrated reader	Sécuriser MIFARE
Language	Multi-language support
Supported Firmware	MR4.10 or later

System

Function keys	3
Supported card types	MIFARE®, Classic UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Logiciel d'adressage
Supported cable type	WCAT 52/54 or equivalent

Communication

Communication type	Kablede
Reading distance	Up to 3 cm
Wiring	RS-485, 4-wire bus

Inputs/Outputs

Inputs	1
Input type	Request to Exit (NO)
Outputs	1
Output type	Open collector (OC), 100 mA max, 15 VDC max.

Electrical

Operating voltage	12.0 to 13.5 VDC (provided by panel)
Current consumption	330 mA at 13.7 VDC, 375mA at 12 VDC (max) 220 mA at 13.7 VDC, 250mA at 12 VDC (average) 70 mA at 13.7 VDC, 80 mA at 12 VDC (standby)

Physical

Physical dimensions	127 x 179 x 20 mm
Net weight	460 g
Colour	Hvid
Mounting type	Vægmontering
Material	ABS plast

Environmental

Operating temperature	0 to +50°C
Relative humidity	up to 95% non-condensing
Environment	Indendør

Regulatory

Certification	EN50131 Grade 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Prodotti compatibili

Categoria	Riferimento	Descrizione
Control Panel	ATS1700-MM	Centrale Everon 1700, IP a bordo, EN grado 3, WebApp, 8 zone a bordo max 48 zone, 4 aree, contenitore metallico medio, multi-lingua
Control Panel	ATS3700-MM	Centrale di sicurezza Everon 3700, IP a bordo, EN grado 3, Web App, da 16 a 256 zone, 16 aree, contenitore metallico medio, multi-lingua
Control Panel	ATS4700-LM	Sempre attiva. Sempre on. Centrale di sicurezza Everon 4700, IP a bordo, EN grado 3, WebApp, 16 zone a bordo, max 1000 zone, 64 aree, contenitore metallico grande, multi-lingua
Control Panel	ATS4700-MM	Centrale di sicurezza Everon 4700, IP a bordo, EN grado 3, Web App, da 16 a 1000 zone, 64 aree, contenitore metallico medio, multi-lingua

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57