# DDI602AM-F1

**Outdoor Dual Technology/AM detector 10.525 GHz 10/20/30m selectable**



# DDI602AM-F1

## Outdoor Dual Technology/AM detector 10.525 GHz 10/20/30m selectable

## Technische specificaties

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Wall mount |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Microwave frequency (nom.) | 10.525 GHz |
| Undercrawl protection | No |
| Alarm time | 5 s |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Wired |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Multiple EOL values |

### Physical

| | |
|---|---|
| Colour | Silver |
| Material | High impact ABS plastic with HDPE cover, UV stabilized |
| Mounting height | 3 to 6 m |

### Environmental

| | |
|---|---|
| Environment | Outdoor |

### Regulatory

| | |
|---|---|
| EN50131 grade | Grade 3 |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57