# ACL875SU-S

## ACL800 Tastatur - freistehend, Aufputzmontage, Silber

### Product description

ACL875SU range is a standalone digital keypad for access control applications with backlight keys, 99 user codes, 2 outputs (relay and transistor) and 1 push button input. These keypads are available in three different color finishes. Authorized users can be assigned specific codes for use in access control applications, electrical switching and arming/disarming alarm systems. The Users can be assigned to activate the first, the second or both outputs. There is a 30 seconds lockout after 8 successive invalid PIN Codes. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall.

### The ACL800 range

ACL875SU range is a standalone digital keypad for access control applications with backlight keys, 99 user codes, 2 outputs (relay and transistor) and 1 push button input. These keypads are available in three different color finishes. Authorized users can be assigned specific codes for use in access control applications, electrical switching and arming/disarming alarm systems. The Users can be assigned to activate the first, the second or both outputs. There is a 30 seconds lockout after 8 successive invalid PIN Codes. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall.



### Einzelheiten

- Innen/Außenbereich
- Staubgeschützt und wasserdicht (IP65)
- Bis zu 99 Benutzercodes
- Codes können 1 bis 8 Stellen lang sein
- Attraktives und zeitloses Design
- Enthält einen Summer
- Dreifarbige LED's
- Aufputzmontage
- Hintergrundbeleuchtung
- Tastenfeld

# ACL875SU-S

## ACL800 Tastatur - freistehend, Aufputzmontage, Silber

## Technische Spezifikationen

### System

| | |
|---|---|
| Max. reader distance to panel | 50 m |
| RTE (Request To Exit) | No |
| CSN (Card Serial Number) | No |
| Custom data model | No |
| No. of LEDs | 3 |
| No. of covers included | 1 |

### Technology

| | |
|---|---|
| Reader type | PIN keypad |
| Read write | No |
| SAM module embedded | No |

### Interface & connections

| | |
|---|---|
| Interface | Wiegand |
| Connector type | Pigtail |
| Pigtail length | 100 cm |

### Tamper type

| | |
|---|---|
| Pry-off tamper | No |
| Opening tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | Yes |
| Stand-alone no. of users | 99 |
| PIN keypad | Yes |
| PIN length | 1 bis 8 Ziffern |

### Electrical

| | |
|---|---|
| Power supply type | VDC |
| Power supply value | 12-24 VDC; 15-24 VAC |
| Current consumption | 60mA @ 12 VDC |

### Physical

| | |
|---|---|
| Physical dimensions | 92 x 51 x 25 mm |
| Net weight | 173 g |
| Shipping weight | 305 g |
| Colour | Silver |
| Material | Moulded aluminium |
| Form factor | Mullion |
| Mounting type | Surface mount |

### Environmental

| | |
|---|---|
| Environment | Indoor, Outdoor |
| Storage temperature | -20 bis +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS |

### Betrieb

| | |
|---|---|
| Tasten | Metallisch beleuchtet |
| Mastercode für die Programmierung | 1 |
| Benutzer-Codes | 99 |
| Grüne LED | Status von Ausgang 1 |
| Rote LED | Status von Ausgang 2 |
| Orangene LED | Programmierstatus und Tastendruck |
| Tastatursperre | Sperrung für 30 Sekunden mit Signalton nach 8 aufeinanderfolgenden falschen Codes |
| Summer | 1 |

### Technologie

| | |
|---|---|
| Ausgänge | 1 Relais (2A) & 1 Transistor (250mA) |
| Relais-Zeit | Selbsthaltend oder zeitgesteuert von 1 bis 99 Sekunden |
| Speicher | EEPROM (die Programmierung ist auch bei Stromausfall sicher) |

### Manipulationstyp

| | |
|---|---|
| Manipulationsschutz | In geöffnetem oder demontiertem Zustand |

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.