6943AMP

Außenvorhangmelder, Triple Technologie, PIR, Radar & Aktiv-Infrarot, mit Antimasking, weiß, ohne T-Halterung, 24GHz

Triple technology inside

This white curtain detector is an outdoor motion sensor and alarm trigger that uses two independent passive infrared detectors and a microwave sensor module. All three sensors must trigger to cause the detector to signal an intruder alarm. In addition it has active infrared technology on board used to detect an anti-masking attempt of the detector. Due to its size it can be smoothly integrated in residential applications.

Easy and quick to install

Programmable options include a variable pulse count and LED able/disable functionality.
Integrated dip switches allow the installer to select out of 4 predefined ranges depending on the application it will be used for.
The product concept caters for 3 possible installations: flat on the wall, 90° perpendicular to the wall using the T-bracket or using a swivel bracket. The two types of bracket can be bought as an accessory.



Einzelheiten

- Bewegungsmelder mit Erfassungsvorhang mit dreifacher Technologie: PIR, Radar und Aktiv-Infrarot
- 4 vordefinierte Erfassungsbereiche
- T-förmiger Montagewinkel und Schwenkbügel als Zubehör
- Für den Außen- und Innenbereich geeignet
- Ansprechende Ästhetik
- Hohe Staub- und Feuchtigkeitsbeständigkeit (IP65)
- 5 Jahre Garantie

6943AMP

Außenvorhangmelder, Triple Technologie, PIR, Radar & Aktiv-Infrarot, mit Antimasking, weiß, ohne T-Halterung, 24GHz

Technische Spezifikationen

General

Technology	Dual
Application type	Wall mount
Anti masking	Yes
Pet immune	No
Camera	No

Detection

Max. detection range	12 m
Detection range selection	3, 6, 9, oder 12 m
Coverage (field of view)	2.8 x 12 m
Microwave frequency (nom.)	24 GHz
Undercrawl protection	No

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Alarm relay characteristic	NC, 50 mA, 24 VDC, Alarmzeit 10 s
Tamper relay characteristic	NC, mit 20 Ω Impedanz, 50 mA
Anti mask relay characteristic	NC, mit 20 Ω Impedanz, 50 mA, Alarmzeit 60 s

Electrical

Operating voltage	9 bis 15 VDC bei max. 40 mA
Current consumption	40 mA

Physical

Physical dimensions	44 x 117 x 41 mm (B x H x T)
Net weight	97 g
Shipping weight	134 g
Colour	White
Mounting height	2 to 4 m

Environmental

Operating temperature	-20 bis 55 °C
Environment	Outdoor
IP rating	IP65

Passiv Infrarot

	Fresnellinse in Kombination mit einem doppelten Pyroelement

Mikrowellenmodul

	X-Band-Radar 24 GHz

Anti-Masking

	Aktiv-Infrarot-Technologie

Impulszahl

	1 oder 2

Temperaturkompensation

	Digital

LED

	Aktivieren/Deaktivieren über Dip-Schalter
	Rot: Einbruchsalarm (PIR- und Radarauslösung)
	Grün : Anti-Masking-Alarm

Montagehöhe

	2 - 2,5 m / bis zu 4 m bei Verwendung einer schwenkbaren Halterung

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.