TESTIFIRE-BP

XTR2 Lithium-ion battery pack

General

The TESTIFIRE-BP is a replacement rechargeable lithium ion battery pack for the Testifire XTR2 smoke and heat tester.



Details

- Replacement, rechargeble battery
- USB-C charger connection
- Fast charge time - 90 minutes
- Safety circuits to prevent over temperature, over current, over charging and deep discharge conditions

TESTIFIRE-BP

XTR2 Lithium-ion battery pack

Technical specifications

Electrical

Operating voltage	10.8 V (35.1 wh / 3250 mAh)
Power source:	USB-C connection
Charging time	50% charge 23°C: < 1 hour
	100% charge 5°C = 3 hours
	100% charge 23°C = 2 hours
	100% charge 40°C = 3 hours

Physical

Colour	Black

Environmental

Vandal proof	No
Operating temperature	5 to 40°C (41 to 104°F)
Storage temperature	-10 to 50°C (14 to 122°F)
Relative humidity	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE

SKU info

Product brand	testifire

Compatible products

Category	Reference	Description
Test Equipment	TESTIFIRE-CHAK	XTR2 Charger Kit
Test Equipment	TESTIFIRE-XTR2	All-in-one connected smoke/heat detector test kit
Test Equipment	TESTIFIRE-XTR2-6M	All-in-one connected smoke/heat detector test kit to 6 m
Test Equipment	TESTIFIRE-XTR2-HEAD	All-in-one connected smoke/heat detector test head

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 October 2024 - 13:42