EVN1700-MM

Centrale Everon 1700, IP a bordo, EN grado 3, WebApp, 8 zone a bordo max 48 zone, 4 aree, contenitore metallico medio, multi-lingua

Always On. Always Aware.

Everon is at the core of the complete security solution that you need. It offers exceptional integration, capability, reliability, installation and user experience. With Everonyour security solution is connected to UltraSync Connected Services, through a fully secure cloud solution.

Exceptional integration

Everon is backwards compatible and easy to migrate from legacy systems, including Advisor Advanced. It offers new APIs, allowing a seamless integration with 3rd party systems. For an even more complete solution, the video surveillance of Aritech is added to the Everon solution via the UltraSync ecosystem.
All Advisor Advanced panels provide integrated access can control where end-user can be grouped. Each group has a separate definition for doors accessible as well as when access is allowed. Being a truly integrated system, additionally users can disarm areas when access to a door is granted.

Exceptional capability

Everon supports up to 1000 intrusion zones, with an optimized cable management system and more power per zone. Everon can handle up to 112 access doors and support the ATS734x /SIM GSM module for connectivity and cloud applications for remote management and diagnosis through UltraSync.

Exceptional reliability

Everon is built upon the successful Advisor Advanced panel: it delivers the highest standard of reliability. With strong cybersecurity levels, Everon is constantly updated based on today's needs.

Exceptional installation

Everon has an exceptional installation, thanks to its multiple tools to make it easy to install: configuration through web browser, new configuration wizards, on-premises or off-premises configuration and incident management, high scalability through the configurator making it more adaptable whether for challenging buildings, extensions or changes of use, and finally, the ability to save and replicate configurations.

Exceptional user experience

Everon provides an optimal user experience with an enriched UX via a new controller platform integrating intrusion, access & video. The user interface has a new contemporary design, including a web application and a touchscreen making it more intuitive and faster to configure. Finally, the panel design has been revisited to fit a new family look across Aritech new generation of products such as the keypad and the upcoming detectors.

Integration to the UltraSync Connected Services ecosystem



Dettagli

- 8 zone a bordo
- Max 48 zone: cablate, via radio o miste
- Everon 1700 gestisce fino a 48 zone a partire dalla versione firmware MR3.2.
- Espansioni di ingressi e uscite plug-in
- Fino a 16 ingressi per sensori inerziali a bordo centrale
- 4 aree
- Fino a 2000 utenti senza controllore di controllo accessi e fino a 65532 utenti con il controllore di controllo accessi
- Porta USB per la configurazione locale
- Multilingua - lingua impostata per ciascuno dei 2000 utenti
- Invio eventi in IP al ricevitore OH-NETREC (GPRS/3G/4G opzionale)
- Connessione Ethernet 10/100 Mb integrata
- Controllo accessi standard senza controllori varco aggiuntivi
- Controllo accessi completo utilizzando i controllori varco CDC4(-EN)
- Fasce orarie per inserimento disinserimento e uscite temporizzate
- Stato centrale live e o ricorrente grazie ai servizi UltraSync
- Configurazione tramite web browser su cellulare, tablet, PC
- Connettori rimovibili e colorati in base alla funzione
- Retro compatibilità con le centrali Advanced e Master
- Alimentatore intelligente
- Bus dati ad alta velocità

We know that the cloud services are the current wave to surf on, and we also believe that it’s the solution to provide you with a multitude of exceptional services, that are secure and easy to handle, for an optimized security system. This is why the UltraSync Connected Services universe is key to our complete range of products, and of course Everon. The connection to UltraSync provides a cloud configurator, cloud backup and restore, external API, firmware upgrade, user management and much much more.

EVN1700-MM

Centrale Everon 1700, IP a bordo, EN grado 3, WebApp, 8 zone a bordo max 48 zone, 4 aree, contenitore metallico medio, multi-lingua

Specifiche tecniche

System

Product line	Everon
Product type	Integrated Access Control
Panel type	Hybrid
Kit	No
No. of keypads / readers	8
Data Gathering Panels (DGP)	7
No. of alarm groups	256
Specified cable	WCAT52 / WCAT54 or equivalent

Inputs

Max no. of inputs	48
Onboard inputs	8
Inputs plug-in expansion	8
ATS1202 support	3

Outputs

No. of outputs	128
No. of onboard outputs	3 electronic outputs + 1 relay

Area

No. of areas	4

User/Cards

Max. no. of users	Up to 65532
Users with name	1000
Max. no. of cards	2000 to 65532
Max. no. of PIN codes	2000 to 65532

Access control

Standard doors on control panel	4
Door groups	128
Floor groups	128
Intelligent doors on 4-door DGPs	28

Communication

Onboard transmission type	IP
Transmission extension	GSM, GSM/GPRS, GSM/GPRS/IP, IP
Databus type	RS485

Event log

Alarm event log	14500
Access event log	10000

Electrical

Operating voltage	24 VDC
Power supply type	230 VAC
Power supply value	230 VAC, -10 to +15%, 50 Hz
Current consumption	650 mA max. at 230 VAC
Mainboard current consumption	110 mA at 24 V (PSU), 160 mA at 12 V (battery)
Max system current	950 mA at 13.8 V ±0.2 V
Max aux power current	2500 mA at 13.8 VDC ±0.4 V
Auto-reset fuses	3 (electrical, 1.3A per use)
Glass break fuses	1 (mains power, T-2A 230 VAC, slow)

Physical

Physical dimensions	315 x 445 x 88 mm
Net weight	4.9 kg (without battery)
Colour	White
Material	Steel (painted)
Housing	Medium metal

Environmental

Operating temperature	-10 to +55°C
Relative humidity	95% noncondensing
Environmental Class	Class II, indoor
IP rating	IP31

Regulatory

EN50131 Grade	Grade 3, with tamper kit
Compliancy	CE
Certification	CE, EN50131 Grade 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Supported versions

Version MR4.3 and above supports up to 48 zones	

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57