# DC116

## Contacto Magnético Montagem Superfície - GAP: 3.6cm, terminais parafuso

### Industrial Surface Mount Contact

The DC116 series features a wider make distance and works better on steel without time-consuming installation of brackets. A wider break distance helps prevent false alarms caused by loose fitting doors.

### Applications

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.




### Detalhes

- Rugged design for industrial applications
- Models for use on steel without time-consuming brackets
- Concealed terminals resist tampering and inadvertent shorting
- Easy clamping terminals speed installation
- Mounting screws included

# DC116

## Contacto Magnético Montagem Superfície - GAP: 3.6cm, terminais parafuso

## Especificações técnicas

### General

| | |
|---|---|
| Application type | Surface mount |
| Contact type | NC |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Wired |

### Physical

| | |
|---|---|
| Colour | Beige |




Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57