RF320I4-N

Magnetkontakt 433 Mhz/ Räckvidd 150 m i öppen terräng. Sänder larm, sabotage, låg batterispänning

Each RF receiver monitors the alarm, battery, tamper and supervisory status of each transmitter. In addition it reports any change in status to the panel, which takes action according to the programmed zone types.



Detaljer

- Learn-Mode Technology
- More than 3 years battery life
- 2 internal reed switches allow for vertical or horizontal mounting
- Wall and cover tamper
- Jumper to select one of the 2 reed switcher or the supervised external input

RF320I4-N

Magnetkontakt 433 Mhz/ Räckvidd 150 m i öppen terräng. Sänder larm, sabotage, låg batterispänning

Tekniska specifikationer

General

Application type	Oberflächenmontage

Wired/wireless

Wired-wireless	Drahtlos
Wireless frequency	433-MHz Ältere Version
Open-air range	150 m

Electrical

Battery lifetime	3 bis 5 Jahre

Physical

Colour	Weiß

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57