EVERON-PCAM

Everon Blinx - Trådbunden PIR-sensor med integrerad kamera

Integrated camera and PIR

The Everon Blinx is a combination of a passive infrared detector (PIR) and a built-in high resolution colour camera as part of the Everon intrusion platform. The Everon Blinx helps to distinguish between true and false alarms thus increasing overall efficiency and improving response to alarms.

As a result, the Everon Blinx is a valuable enhancement to any residential or commercial security system, offering visual verification of alarm events. This enables operators at Central Monitoring Stations to prioritize follow-up actions more effectively.

The Everon Blinx cylindrical shape and curved front surface give it a sleek, modern appearance that blends into various environments. The front-facing camera lens subtly integrated, indicates its focus on discrete surveillance.



Camera

The camera’s field of view and contrast are optimized to deliver high-quality video, even in low-light or nighttime conditions, eliminating the need for manual adjustments.
Monitoring stations receive recorded streaming video rather than a series of still images, enabling more effective alarm verification. Additionally, end-users can access the Everon Blinx live video or recorded video clips through the App when connecting to the Everon security system.

PIR

The Everon Blinx features a 12 meter passive infrared detection range. Powered by Aritech’s advanced mirror optics and neural technology, the Everon Blinx brings high detection accuracy.

Installation

For proper installation, we recommend using a Cat 5 twisted pair Ethernet cable for the communication between the Everon Blinx and the Everon panel. Up to 6(*) Everon blinx's can be connected to the panel's fast databus BUS3 and they can easily be enrolled through the panel’s web application.

Detaljer

- Upp till maximalt 6 Everon Blinx per Everon-system (*)
- 4-tråds bussanslutning som stödjer avstånd upp till 100 meter
- 9 högdensitets spegelgardiner för exakt rörelsedetektering
- Använder UltraSync-protokoll för säker och tillförlitlig kommunikation
- Automatisk växling mellan dag- och nattläge
- Videoströmning i realtid via Edge API direkt till CMS
- Inspelning före och efter larmhändelse
- Integrerad med Advisor Advanced-mobilapplikationen
- Konfiguration via Everon webbapplikation

EVERON-PCAM

Everon Blinx - Trådbunden PIR-sensor med integrerad kamera

Tekniska specifikationer

General

Technology	PIR
Anti masking	No
Pet immune	No
Camera	Yes
Detector start-up time	60 s
Motion / event triggered video clip	Triggered by control panel Linked to zone
Pre-recording	5 sec.
Post-recording	10 sec.
Video transmission	Via panel ethernet connection

Detection

Detection range	12 m
No. of curtains	9
Viewing angle	78 degrees
Upright target speed range	0.1 to 3.0 m/s
Crawling target speed	0.2 m/s min.

Wired/wireless

Wired-wireless	Wired

Electrical

Power supply value	9 to 28 VDC (12 VDC nominal)
Current consumption	Night mode: 142 mA max., day mode: 100 mA max.
Wiring	Everon fast data bus (BUS3) (*) up to 6x Everon Blinx's of which max. 5x powered from BUS3

Physical

Physical dimensions	128.0 x 64.4 x 68.0 mm
Net weight	185 g
Colour	White
Mounting height	2 to 3 m

Environmental

Operating temperature	−10 to +55°C
Relative humidity	95% max., noncondensing
IP rating	IP30 IK04

Regulatory

EN50131 grade	Grade 2
Certification	EN50131 Grade 2, INCERT, SBSC

Camera

Video resolution	1080p (1280 x 1080)
Colour modes	Colour / Black and white
Night illumination	Up to 7 m
Frame rate	5 fps (640 x 540), 10 fps (1280 x 1080)
Video format	RTSP

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57