AS36RIM

Sounder Beacon Rim with "Fire" text (English)

General

The AS36RIM is an aesthetic surround AS360, AS2360, FA360 and FA2300 series VADs, visual indicators, sounders and combination units. It allows for the selected product to be displayed with "FIRE" text, in the selected language.

The AS36RIM may be retro fitted to compatible deep base devices in the range, and allows for convenient and clear visual verification of the location of fire notification equipment on any installation.



Installation

Due to an innovative design, the text orientation of the AS36RIM may either be horizontal or vertical, depending on the application requirements. A locking mechanism prevents the orientation position from being changed once the notification device has been installed.

Designed to accommodate both surface and rear cable entry, the selected, deep base notification device continues to maintain its IP rating as before. The AS36RIM in no way affects the operation or mounting options of the selected notification device, and may be used for compatible addressable and conventional notification devices.

Additional text

Because of the flat surface areas, logos and/or additional text may be added on site as required.

Detaljer

- Easy to install
- Provides and aesthetic surround for fire notification devices
- Horizontal or vertical installation
- Locking mechanism to lock orientation
- Additional flat surfaces for logos or text

AS36RIM

Sounder Beacon Rim with "Fire" text (English)

Tekniska specifikationer

Physical

Colour	Red
Mounting type	Wall mount
Mounting position	Wall
Material	High impact polycarbonate

Environmental

Vandal proof	No
Environment	Indoor, Outdoor

Regulatory

Compliancy	CE, REACH, RoHS 2

Kompatibla produkter

Kategori	Referens	Beskrivning
Notification device	AS363	Röd siren med låg sockel 32 toner, IP21 för CPD-godkänd 17-60 VDC, 4-41 mA. Spänningsmatning 9-60 VDC, 4-41 mA, 90-106 dBA vid 1 m
Notification device	AS363W	Vit siren med låg sockel 32 toner, IP21 för CPD-godkänd 17-60 VDC, 4-41 mA. Spänningsmatning 9-60 VDC, 4-41 mA
Notification device	AS364	Röd siren med lhög sockel 32 toner, IP65 för CPD-godkänd 17-60 VDC, 4-41 mA. Spänningsmatning 9-60 VDC, 4-41 mA, 90-106 dBA vid 1 m
Notification device	AS364M	Sounder, Multi Tone, Deep Base, Mains Powered
Notification device	AS364W	Fire Sounder, Multi Tone, Deep Base, White
Notification device	AS366	Siren med låg sockel och blixtljus
Notification device	AS367	Siren med hög sockel och blixtljus

EDWARDS
Built for Resilience

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57