DT2063N

Termo detektor med ekstern LED udgang



DT2063N

Termo detektor med ekstern LED udgang

Tekniske specifikationer

General

Addressing method	Rotary switch

Electrical

Power supply type	Loop-Stromversorgung

Detection

Monitoring	Alarm threshold
Alarm temperature (typical)	> +40°C

Physical

Colour	Wolkenweiß (RAL 9001)
Mounting type	Deckenmontage
Material (body)	Plastik

Environmental

Vandal proof	No
Application temperature (typical)	+25°C
Environment	Drinnen

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Kompatible produkter

Kategori	Reference	Beskrivelse
Detection device	DB2002	2000 Serie Detektor sokkel 10 cm, 5 Terminaler
Detection device	DB2004	2000 Serie Detektor sokkel dyb, 10 cm, 5 Terminaler
Detection device	DB2016	2000 Serie isolator sokkel
Notification device	AI672	Fjernindikator
Notification device	AI673	Fjernindikator med lyd
Notification device	DB2368IAS-W	2000 Seriens Sokkelsirene m/Isolator - HVID

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57