ACI421-PIN

OSDP reader with PIN keypad, Mifare Desfire EV1/2/3, CSN & Bluetooth

Product overview

The ACI42x-W range of Wiegand readers provides an attractive reader in slim line or standard design supporting cards with secure Mifare Desfire EV1/EV2/EV3 security. In addition the reader provides for onboard Bluetooth (BLE) support. The ACI42x-PIN variants include a PIN keypad.

Secure readers

The ACI42x-W range supports security from the card up to the reader when Mifare Desfire EV1/EV2/EV3 cards are encrypted.



Details

- Secure OSDP Mifare Desfire EV1/EV2 reader with PIN keypad
- Supports Mifare Desfire EV1/EV2 custom cards and CSN, as well as other Mifare CSN cards
- Address and other settings through configuration cards
- Robust molded plastic housing
- Indoor or outdoor mounting
- Request to exit input and one output
- Bluetooth BLE onboard
- Supported on CDC4 range of Door/Lift controllers

ACI421-PIN

OSDP reader with PIN keypad, Mifare Desfire EV1/2/3, CSN & Bluetooth

Technical specifications

System

Reading distance	up to 5 cm depending on technology used and environment
Max. reader distance to panel	1 km from control panel
CSN (Card Serial Number)	Yes
Custom data model	Yes
Supported card types	Mifare Classic 7 Byte UID, MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® Plus UID, NFC (UID)
Addressing type	Kartenadressierung
No. of LEDs	3 x multi-color

Technology

Reader type	Smartcard
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (benutzerdefinierte Daten), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Benutzerdefinierte Daten), MIFARE Plus (CSN), NFC (CSN)
Supported technology 2.4 GHz	Bluetooth
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Byte (nicht eindeutig), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70)

Interface & connections

Interface	OSDP V2 Sicherer Kanal
Connector type	Zopf
Pigtail length	3 m

Inputs/outputs

Inputs	Aufforderung zum Beenden
Outputs	1 Open Collector (50 mA)

Tamper type

Opening tamper	Yes

Operation

PIN keypad	Yes
PIN length	Depending on controller

Electrical

Operating voltage	10 to 30 VDC
Current consumption	50 mA @ 13.8 VDC normal 120 mA @ 13.8 VDC max.

Physical

Physical dimensions	127 x 85 x 28 mm
Colour	Schwarz
Material	Plastik
Form factor	Standard
Mounting Type	Oberflächenmontage

Environmental

Operating temperature	-30 to +55°C
Relative humidity	max 95% noncondensing
Environment	Drinnen, Draussen
IP rating	IP67 IK09

Regulatory

Compliancy	CE
Certification	CE

Compatible products

Category	Reference	Description
Accessories	ACI421-MNT-33	Angled mounting plate for ACI421, 33° degress angle

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 15:13