# 9-10928

## Patress Sampling Point Assembly - complete

### Description

The 9-10928 is a patress sampling point. It is supplied complete with a 27mm diameter t-union, to which the flexible sample pipe connects. The flexible sampling pipe has a diameter of 10mm and is 1m long. At the end of the flexible sampling pipe, the sampling point is connected which is mounted onto the false ceiling with two screws.



# 9-10928

## Patress Sampling Point Assembly - complete

## Technical specifications

### Sampling pipe

| | |
|---|---|
| Length | 1 m, 10 mm (outer diameter) |

### Physical

| | |
|---|---|
| Physical dimensions | 65 mm (Diameter of sampling point) |
| Colour | Rot, Weiß |
| Mounting type | Eingesetzt |

### Environmental

| | |
|---|---|
| Environment | Drinnen |

### Regulatory

| | |
|---|---|
| Certification | EN54-20 |

### Samlping point

| | |
|---|---|
| diameter | 65 mm |
| screw hole spacing | 50 mm |

### T-union

| | |
|---|---|
| diameter | 27 mm (inner) |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 8 April 2024 - 14:32