DD669

Dual Detector with 18 curtains of 20 m NC Relay



Details

- Dual motion sensor
- Step & Gliding Focus Multi Curtain mirror optic
- Plug-in electronics
- Sealed optics
- 4D processing for reduced nuisance alarms
- Selectable coverage pattern using mirror masks
- Additional bi-curtain processing for harsh environment
- No adjustment required for different mounting heights
- EN50131-2-4 Grade 2 certified
- Several European approvals

DD669

Dual Detector with 18 curtains of 20 m NC Relay

Technische specificaties

General

Technology	Dual
Application type	Deckenmontage
Anti masking	No
Pet immune	No
Camera	No
Signal processing	4D
Pry-off tamper kit	ST400 (optional)

Detection

Max. detection range	20 m
Detection range	20 m
No. of curtains	18
Coverage (field of view)	360°
Microwave frequency (nom.)	5.8 GHz
Undercrawl protection	No
Alarm memory	Yes
Alarm time	3 sek

Wired/wireless

Wired-wireless	Verdrahtet

Inputs/outputs

Alarm relay characteristic	NC when energised
Tamper relay characteristic	NC when cover closed
Relay configuration	Isoliert oder 4k7 EOL
Remote control lines	Tag/Nacht, Gehtest

Electrical

Power supply type	12 VDC
Power supply value	9 to 15 VDC (12V nominal)
Current consumption	12 mA

Physical

Colour	Weiß
Mounting height	2,5 bis 5 m

Environmental

Operating temperature	-10 to +55°C
Relative humidity	95.00%
Environment	Drinnen

Regulatory

EN50131 grade	Klasse 2
Certification	VdS



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57