ATS1180-STK

Lexan sticker spare part for the ATS1180 and ATS1180M

Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Axon and Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Axon or Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

Communication

The reader communicates in a secure way over the ATS LAN databus to Axon or Advisor control panels using AES encryption, securing the data from the card until being processed.

Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.



Details

- Secure ATS MIFARE DESFire EV1/EV2/EV3 reader
- Prepared for Mobile Credentialing using Bluetooth
- Supports Secure Mifare (secure mode) or Mifare 4 or 7 byte CSN/UID (Unsecure mode)
- Use secure ATS145x series cards or customer cards
- Secure communication using AES-128 bit encryption between reader and Axon / Advisor Advanced / CDC4 control panel
- Robust molded plastic housing in slim design
- Indoor or outdoor mounting
- ATS bus interface
- Request To Exit input
- Open Collector Output (door open)
- Supported as of Advisor Advanced MR4.9 and from Axon MR1.0
- NFC prepared for configuration purposes

ATS1180-STK

Lexan sticker spare part for the ATS1180 and ATS1180M

Technical specifications

System

Max. reader distance to panel	1500 m
CSN (Card Serial Number)	Yes
Custom data model	Yes

Tamper type

Pry-off tamper	Yes

Operation

Stand-alone	No
PIN keypad	No

Physical

Colour	Sort
Material	Plastic
Form factor	Slimline
Mounting Type	Montage en surface

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 10:11