ACL800-RDRMF-GRAY

ACL800 MIFARE READER - WIEGAND, SURFACE MOUNT, BLACK



ACL800-RDRMF-GRAY

ACL800 MIFARE READER - WIEGAND, SURFACE MOUNT, BLACK

Spécifications techniques

System

Max. reader distance to panel	152 m
RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	No
No. of LEDs	1
No. of covers included	1

Technology

Reader type	Carte à puce
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE, DESFire (CSN), MIFARE, DESFire EV1 (CSN), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE Ultralight (CSN)
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 octets (S50), 7 octets (S70)
Read write	No
SAM module embedded	No

Interface & connections

Interface	Wiegand
Connector type	Zopf
Pigtail length	90 cm

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	No
PIN keypad	No

Electrical

Power supply type	VDC
Power supply value	5 to 24 VDC
Current consumption	100 mA at 24 VDC 30 mA at 24 VDC

Physical

Net weight	120 g
Shipping weight	170 g
Colour	Schwarz
Material	ABS
Form factor	Mullion
Mounting type	Montage en surface

Environmental

Environment	Drinnen, Draussen
Storage temperature	-20 to +50°C

Regulatory

Compliancy	CE, RoHS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57