SMA-ICLASS-WR

SIGMA Series - Outdoor/WR/IP65, Multi-factor Bio/Card/PIN/BioPIN (3k users incl.), HID iClass, 1M logs storage capacity, PoE incl.



UNRELEASED

SMA-ICLASS-WR

SIGMA Series - Outdoor/WR/IP65, Multi-factor Bio/Card/PIN/BioPIN (3k users incl.), HID iClass, 1M logs storage capacity, PoE incl.

Specifiche tecniche

System

RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	Yes

Technology

Reader type	Biométrique
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	iCLASS (CSN), iCLASS (données personnalisées), iCLASS SEOS
Read write	Yes
SAM module embedded	No

Biometric

Biometric type	Empreinte digitale
Biometric sensor type	Optique

Interface & connections

Interface	Ethernet, OSDP V2, OSDP V2 canal sécurisé, RS-485, USB, Wiegand
Connector type	Netværk, Terminal strip

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	Yes
PIN keypad	Yes

Electrical

Power supply type	VDC

Physical

Colour	Sort
Material	Polycarbonat
Form factor	Overdimensioneret
Mounting type	Montage en surface

Environmental

Vandal proof	No
Environment	Indendør, Udendørs

Regulatory

Compliancy	CE, FCC, REACH, RoHS, UL 294, WEEE

UNRELEASED

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57