DD1012AM-N

Detector Dupla tecnologia dupla de 12 m, 9 cortinas, Anti-Máscara

Patented range gated radar technology

Motion sensors of the DD1000 Series incorporate a KSG Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.
The radar operates on 5.8 GHz frequency.

The DD1012AM-N motion sensor incorporates a new digital pyro for an improved signal quality and a better immunity to electrical interferences.

PIR technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.
Within our DD1012 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.

Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.
But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

Anti-masking (optical and radar)

The use of Active Infrared and radar technology results in a superior anti-masking functionality that supervises the motion sensor on the inside and outside. Radar verification prevents from having unwanted AM alarms caused by e.g. insects. In advanced setting the AM alarm is held until the effective source of the anti-masking (e.g. spray,



Detalhes

- Tecnologia patenteada de radar de alcance selecionável que define claramente o limite de deteção do radar
- Tecnologia PIR com óptica de cortina de espelho patenteada
- Variante anti-mascaramento que utiliza tecnologia de infravermelhos activos e de radar para proteger contra acções de sabotagem fora e dentro do sensor de movimento
- Decisão de alarme inteligente baseada na classificação do sinal do alarme PIR e de radar
- Auto-diagnóstico automático contínuo em todas as tecnologias
- Modo verde: opção para desligar a tecnologia de radar quando o sistema de segurança não está armado
- Detentor de várias aprovações de segurança, incluindo EN Grau 3
- Incorpora um novo piro digital que detecta as flutuações de temperatura com elevado grau de precisão

tape,…) has been removed. Even partial masking – so going beyond the EN Grade III standard – will be detected when in advanced setting.

Other members of the family

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity. The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

DD1012AM-N

Detector Dupla tecnologia dupla de 12 m, 9 cortinas, Anti-Máscara

Especificações técnicas

General

Technology	Double
Application type	Fixation murale
Anti masking	Yes
Pet immune	No
Camera	No
Pry-off tamper kit	Embarqué
Detector start-up time	60 s

Detection

Max. detection range	12 m
Detection range selection	4, 6, 9 ou 12 m seleccionáveis através de interruptores dip
No. of curtains	9
Coverage (field of view)	78°
Microwave frequency (nom.)	5.8 GHz
Max. microwave output (at 1m)	0.003 µW/cm²
Undercrawl protection	Yes
Target speed range	0.2 a 3.0 m/s
Alarm memory	Yes
Alarm time	3 secondes
Peak-to-peak ripple immunity	2 V (a 12 VDC)

Wired/wireless

Wired-wireless	Verdrahtet

Inputs/outputs

Alarm relay characteristic	NC, 80 mA 30 VDC, Form A
Tamper relay characteristic	NC, 80 mA 30 VDC, Form A
Relay configuration	Valeurs EOL multiples
Remote control lines	Jour/Nuit, Test de fonctionnement

Electrical

Power supply value	9 a 15 VDC (12 V nominal)
Current consumption	10 mA nominal

Physical


Physical dimensions	126 x 63 x 50 mm
Net weight	120 g
Colour	Weiß
Mounting height	1.8 à 3 m

Environmental

Operating temperature	-10 a +55°C
Relative humidity	95% sem condensação
Environment	Drinnen
IP rating	IP30 IK04

Regulatory

EN50131 grade	Grad 3
Compliancy	CE
Certification	INCERT, NFA2P



Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57