N-IO-SBX-1G

Single module box with DIN rail (small)

General

The N-IO-SBX-2G is a surface mount enclosure with DIN rail fitted. With its halogen free, high impact and splash proof design, it is suitable for indoor and outdoor applications. Multiple, self sealing cable entries are available from all sides, making it possible to install wherever a housing is required.

Application

The N-IO-SBX-1G is intended for use with small footprint Excellence series control modules such as:

- KE-IO3101
- KE-IO3101-M
- KE-IU3110



Details

- Easy surface mounting
- Multiple PG 21 cable entry points from all sides
- Preinstalled DIN-rail for easy module installation
- Preinstalled cable screen termination
- Splash proof
- IK08 impact resistant
- Halogen free

N-IO-SBX-1G

Single module box with DIN rail (small)

Technical specifications

General

Compatibility	Excellence series small footprint modules

Physical

Physical dimensions	150 x 110 x 70 mm (L x W x H)
Colour	Grå
Mounting type	Montaggio a superficie
Cable entries	10 x 29 mm Ø
Material	Engineering plastic

Environmental

Vandal proof	No
Operating temperature	up to +70°C
Environment	Indendør, Udendørs
IP rating	IP55

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE

Compatible products

Category	Reference	Description
Interface unit	KE-IO3101	Excellence series intelligent addressable 1 output unit with isolator
Interface unit	KE-IO3101-M	Excellence series intelligent addressable mains switching output unit with isolator
Interface unit	KE-IU3110	Excellence series intelligent addressable 1 input unit with isolator

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 14 August 2025 - 11:35