POC252-1CXP-1T

1-Port IP over Coax Extender with PoE-AT (switch end)

Overview

The IFS® Power over Coax Network Switches and Media Converters by Interlogix® are designed to transmit both Ethernet data and PoE over coax cable up to 1 km (3,280 ft). This solution provides a cost-effective approach by reducing installation cost and increasing ROI by utilizing existing coax to migrate an existing analog video system to an IP video surveillance system.

The PoC Network Switches also provide built-in PD-alive monitor health and status of an IP camera. In addition, this solution eliminates the need for providing local power at an IP PoE camera location.



• The POC2502-8CXP-2T-2S is an 8-port Power over Coax Managed Switch that supplies data and power transmission on coax via BNC ports. In addition, the two RJ45/SFP Gigabit combo ports provide a connection to an Ethernet network.

• The POC2502-16CXP-2T-2S is a 16-port Power over Coax Managed Switch. The switch supplies data and power transmission on coax via BNC ports as well as two RJ45/SFP Gigabit combo ports for connection to an Ethernet network.

• The POC252-1CX-1P Power over Coax Media Converter is for use at the camera end to convert the data/power from the coax. The switch provides 10/100Mbps data and POE-af/at compliant power on the RJ45 port for an IP camera.

• The POC252-1CXP-1T Power over Coax Media Converter transmits data and injects power over coax for use with the POC252-1CX-1P. This is used to deploy a single IP camera on a length of coax cable and a multi-port BNC switch is not needed. This media convertor is for use at the switch end of a system.

Details

- 1-port (COAX) with up to 36W power output
- Auto-negotiation and auto-MDI/MDI-X
- IEEE 1901 communication Standard
- Wavelet-OFDM modulation
- 128-bit AES security encryption
- Daisy-chain (up to 3 devices on one link)
- Half-duplex back pressure and IEEE802.3x full-duplex pause-frame flow control
- Remote power up to 1 km
- Compatible with POC252-1CX-1P (Camera End) Media Convertor

POC252-1CXP-1T

1-Port IP over Coax Extender with PoE-AT (switch end)

Technical specifications

General

Technology	IEEE1901
Compatible with MCR rack	No

Connections

Coax ports	1
Connector	BNC
RJ45 ports	1
Port type	10/100
Fault relay output	Nej

Electrical

Power supply type	52 til 56 VDC
Power consumption	Max. 34 W (Full PoE load)
PoE/PoE+	PoE-at (Power over Coax)
PoE power budget	30.8 W (via PoE-at switch) 36 W (via PSU)
Redundant power	No

Physical

Physical dimensions	94 x 70 x 26 mm
Net weight	375 g
Colour	Sort
Mounting type	Vægmontering

Environmental

Operating temperature	-10 to +60°C
Storage temperature	-40 to 75°C
Relative humidity	0 to 95% noncondensing

Physical Ports

Port Configuration	Auto MDI/MDI-X
Port Speed	Auto-negotiate
LED Indicators and Switch	

Regulatory

Regulatory Standards	FCC Part 15 Class A, CE
IEEE Standards	IEEE 802.3 Ethernet
	IEEE 802.3u Fast Ethernet
	IEEE 802.3af Power over Ethernet
	IEEE 802.3at Power over Ethernet Plus

Power over Ethernet

PoE Standard	IEEE 802.3af / 802.3at PoE
PoE Power Supply Type	End-span
PoE Power Budget	Up to 25 W via Coax
PoE Power Output Via Coax Port	Max. 30.8 W (via PoE Switch) 36 W (via PSU)
Power Pin Assignment (RJ45)	1/2(+), 3/6(-)
Power Pin Assignment (COAX)	BNC center pole : DC+ / Hi, BNC shield : DC - / Lo

IP Over Coax Interface

Cabling	Coaxial cable: 75 ohm, RG-6/U cable (Improved performance)
	RG-6/U cable, less than 12 Ohm/1,000 ft.
	RG59/U cable, less than 30 Ohm/1,000 ft.
Ethernet Communication Standard	IEEE1901
Modulation Type	Wavelet-OFDM
Security	128-bit AES encryption
Frequency Band	2 to 28 MHz

Data Rate (Upload/Download)*

20 m	93 / 93 Mbps
400 m	93 / 92 Mbps
600 m	92 / 88 Mbps
800 m	83 / 75 Mbps
1000 m	74 / 55 Mbps

Typical Power Over Coax*

200 m	29 W (5 VDC in) 16.9 W (PoE+ in)
400 m	22 W (56 VDC in) 14.3 W (PoE+ in)
600 m	13 W (56 VDC in) 10.2 W (PoE+ in)
800 m	10 W (56 VDC in) 8.3 W (PoE+ in)
1000 m	8 W (56 VDC in) 7.1 W (PoE+ in)
* Based on RG-59 Bare Copper cable:	Data rate and power performance is subject to the quality of cable used and environmental factors.

Maximum Distance

PoE+ output	200 m
PoE output	600 m
Without PoE (Data only)	1,200 m

POC252-1CXP-1T

1-Port IP over Coax Extender with PoE-AT (switch end)



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:24