ASC367

Conventional Ceiling Mount VAD, Multi tone, Deep base - RED with RED flash



Details

- High sound output with Pulse Alert™ technology
- 32 Tones user selectable
- Automatic syncronisation
- Volume control and adjustable flash rate
- Anti-Tamper locking mechanism
- Deep mouting base with side cable entry and wiring to the base
- Seperate sounder and beacon and control
- EN54:3 and EN54:23 approved, CPR Certified

ASC367

Conventional Ceiling Mount VAD, Multi tone, Deep base - RED with RED flash

Technische specificaties

Electrical

Current consumption	Sounder: 5.1 mA, Beacon: 20 mA @ 0.5 Hz / 40 mA @ 1 Hz

Physical


Net weight	215 g
Colour	Rød
Mounting type	Montaggio su base
Mounting position	Soffitto
Mounting base	Profondo
Material	Policarbonato alto impatto

Environmental

Operating temperature	-25 to +70°C
Relative humidity	5 to 95%
Environment	Indendør, Udendørs
IP rating	IP65

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	EN54-23, EN54-3



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57