IU2050NC

2000 Series IO Unit 1 In

General

The IU2050NC is a 2000 series addressable single input unit with selectable line supervision to monitor normally open or normally closed contacts. The unit is loop powered and supplied in an enclosure for surface mounting applications.

The 2000 series loop powered input/output modules are designed to provide much needed flexibility to input monitoring and output switching. These modules, combined with the powerful features of the Aritech addressable fire panels, give the user versatility for diverse applications.


Applications

The addressability of the IU2050NC allows the identification of the exact location of the switch activation. It may be used with applications requiring fast response such a conventional manual call points, door monitors etc. where a change of state needs to be reported within 3 seconds. Alternatively it can be used in any application where a point needs to be made addressable and supervised on the fire panel.

Installation

The IU2050NC is connected to and Aritech CIE via a two-wire communication loop that provides power and control data. The single input module address is conveniently set with rotary switches. The address setting is non-volatile and will not be lost in the event of a power failure.

The single input module utilizes an advanced digital data communications protocol that ensures the integrity of the data communications with extensive error correction algorithms.



Details

- Loop powered
- Programmable input state
- Easy numeric addressing
- EN54 approved and CPR certified

IU2050NC
2000 Series IO Unit 1 In

Technische specificaties

General

Compatibility	2000 Series Systems
Addressing method	Rotary switch

Electrical

Operating voltage	17 to 28 VDC
Current consumption	<205 µA (Quiescent) <270 µA (Active)
Communication voltage	4 to 10 V

Input

Input quantity	1
Input type and rating	Supervised
Termination resistor	150 kΩ, ¼ W, 5%

Physical

Physical dimensions	120 x 90 x 35 mm
Net weight	144 g
Colour	Grigio chiaro
Mounting type	Montaggio a superficie
Cable entries	1
Material	Plastic

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-20 to +60°C
Relative humidity	10 to 95% noncondensing
Environment	Indendør
IP rating	IP40

Regulatory

Compliancy	CE, REACH, RoHS 2
Certification	BOSEC, VdS
Standards	EN54-18

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	ISM-95	2000/900 Series Stand Alone Loop Isolator (CPD Certified)
Interface unit	IO2034NC	2000 Series IO Unit 4 In / 4 Out
Interface unit	IU2055NC	Grenzwerttechnikmodul der 2000er Serie, inkl. Gehäuse
Interface unit	IU2080NC	Signalgebermodul der 2000er Serie, inkl. Gehäuse

KIDDE GLOBAL SOLUTIONS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57