FE323-N

Magnetic lock 2430 N, Mega-LED and Relay

Mega-LED

This electromagnet is part of the new series of magnetic locks equipped with a “Mega-LED” allowing to see the LED status from a much further distance.

Security, quality and design

Security, safety and design using high quality materials, ensuring maximum strength without any residual magnetism or corrosion and proven holding force.



Details

- Strong design with high-end finish
- Corrosion proof: salt spray test (ISO 9227, ASTM B 117-90) at 35% for 96 hours
- No residual magnetism
- Built-in MOV surge protection
- L bracket and Z + L bracket set available

FE323-N

Magnetic lock 2430 N, Mega-LED and Relay

Technical specifications

General

Product type	Magnetic lock

Holding force

Holding force kgf (Kilogram force)	243
Holding force N (Newton)	2430

Monitoring & status

Monitored	Yes
LED indicator	Yes
Door status switch	No

Electrical

Operating voltage	12 / 24 V
Current consumption	500 / 250 mA

Physical

Physical dimensions	238 x 26 x 48 mm
Net weight	~2 kg
Colour	Aluminium

Environmental

Operating temperature	-40 to +60°C

Main features

Mounting	Surface
Locking monitoring	Large L shaped LED for long distance status + Relay
Door position monitoring	No
Corrosion Proof	Salt spray test. ISO 9227, ASTM B-117 90
Residual magnetism	Guaranteed no residual magnetism
Built-in MOV Surge Protection	Yes

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 March 2026 - 12:37