# SC-52-0200-0001-99

## SmartCell Information Manual Call Point

### Overview

The SmartCell Information Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel. The device when activated, sends an information alert to the Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.




### Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism
- NOT FOR FIRE OR SECURITY APPLICATIONS

# SC-52-0200-0001-99

## SmartCell Information Manual Call Point

## Technical specifications

### General

| | |
|---|---|
| Status indication | LED |
| Wireless frequency | 868 MHz |
| Compatibility | SmartCell |

### Electrical

| | |
|---|---|
| Batteries | 2 x 3.6 V lithium thionyl chloride batteries.<br>Fanso: ER14505M<br>HCB: ER14505M (HCB-JS-TZ-02-547) |

### Physical

| | |
|---|---|
| Physical dimensions | 92 x 97 x 47 mm (W x H x D) |
| Net weight | 0.2 kg |
| Colour | Hvid |
| Mounting type | Vægmontering |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +55°C |
| Storage temperature | -10 to +55°C (without batteries) |
| Relative humidity | 95% noncondensing max. |
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CPR |
| Standards | EN54-13<br>EN54-25 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 30 July 2025 - 17:41