# DDI602AM-F2

**Outdoor Dual Technology/AM detector 10.587 GHz 10/20/30m selectable**



# DDI602AM-F2

## Outdoor Dual Technology/AM detector 10.587 GHz 10/20/30m selectable

## Spécifications techniques

### General

| | |
|---|---|
| Technology | Dualna |
| Application type | Uchwyt ścienny |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Microwave frequency (nom.) | 10.587 GHz |
| Undercrawl protection | No |
| Alarm time | 5 sek |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Verdrahtet |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Wiele wartości EOL |

### Physical

| | |
|---|---|
| Colour | Silber |
| Material | Hochschlagfester ABS Kunststoff mit HDPE Abdeckung, UV stabilisiert |
| Mounting height | 3 do 6 m |

### Environmental

| | |
|---|---|
| Environment | Draussen |

### Regulatory

| | |
|---|---|
| EN50131 grade | Grad 3 |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57