PM844-A

Boxed switch mode power supply, 12 VDC, 4 A, with fault outputs



Details

- Continuous full rated current to load
- Additional 0.5 A (average) to charge standby battery
- High efficiency electronics for reduced running costs and lower operating temperatures
- Modular construction for ease of maintenance and installation
- Full electronic short circuit and overload protection on load output under mains operation
- Lid opening tamper detection
- Increased room space for additional PCBs or cables

PM844-A

Boxed switch mode power supply, 12 VDC, 4 A, with fault outputs

Technische specificaties

General

Fuse(s)	230 VAC input 3.15A, 12/24V output 4 A

Electrical

Mains input	100 to 240 VAC

Output

Power output voltage	13.8 VDC
Output ripple	150 mV pk-pk max
Power output current mains	4 A

Battery

Max. Battery capacity	18 Ah 12 V
Battery charge current	0.5 A

Physical

Colour	Hvid
Form factor	Stål kabinet

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57