ACL800-RDRMF-GRAY

Gray Mifare Surface mount Reader



Details

- Indoor/outdoor
- Dust proof and water-resistant (IP65)

ACL800-RDRMF-GRAY

Gray Mifare Surface mount Reader

Technische specificaties

System

Max. reader distance to panel	152 m
RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	No
No. of LEDs	1
No. of covers included	1

Technology

Reader type	Smart Card
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE Ultralight (CSN)
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Byte (S50), 7 Byte (S70)
Read write	No
SAM module embedded	No

Interface & connections

Interface	Wiegand
Connector type	Svinesvans
Pigtail length	90 cm

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	No
PIN keypad	No

Electrical

Power supply type	VDC
Power supply value	5 to 24 VDC
Current consumption	100 mA at 24 VDC 30 mA at 24 VDC

Physical

Net weight	120 g
Shipping weight	170 g
Colour	Sort
Material	ABS
Form factor	Mullion
Mounting type	Montagem em superfície

Environmental

Environment	Indendør, Udendørs
Storage temperature	-20 to +50°C

Regulatory

Compliancy	CE, RoHS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57