RF-DC101-K4

Wireless surface mount, white, 433 Mhz, 80+

Operation

In this series we are using KGS's 80+ wireless protocol in a 433 Mhz frequency set-up, which allows for a better wireless indoor range. This 80+ protocol helps ensure security approvals.
This wireless door window sensor, which has 2 reed switches, protects anything that opens and closes such as doors, windows and cabinets. You can monitor any supervised contact in such a way that hardwired devices become wireless in a fraction of time.
The sensor is equipped with a wall and cover tamper for additional security.
This series comes in a white and a mahogany version and also has accessories in both colors.



Details

- 80+ wireless protocol using 433 Mhz for improved indoor range
- 5-years battery life
- Battery pull-tab concept
- Selectable reed switches
- Additional terminal block
- Range of accessories : two types of spacers and a stronger magnet
- Holding EN and Incert certificates

RF-DC101-K4

Wireless surface mount, white, 433 Mhz, 80+

Technical specifications

General

Application type	Ytmontering
Contact type	Reed switch

Wired/wireless

Wired-wireless	Trådløs
Wireless frequency	433 MHz LoNa
Open-air range	400 m
Operating gap	7 to 13 mm

Electrical

Power consumption	max 70 mA at 3 V
Voltage	3.0 V
Contact power	Maximum power output : 10 mW
Batteries	1300 mAh (DL123A)
Battery lifetime	>5 years with supervis. signal per 15 min. and 4 activations/hour

Physical

Dimensions contact / sensor	101 x 31 x 28 mm
Net weight	59 g
Colour	Hvid

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-34 to +60°C
Relative humidity	0 to 90% noncondensing

Regulatory

EN50131 grade	Lønklasse 2

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 15:17