BS130N

Droge accu, 12 V, 12 Ah, VdS



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS130N

Droge accu, 12 V, 12 Ah, VdS

Technische specificaties

General

Product type	Forseglet blybatteri

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	12 Ah
Internal approx. resistance	13 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	3.6 A
Max. discharge current	60 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Material	ABS
Terminal type	Fast-on 6.35 mm

Environmental

Fire retardant	No
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	VdS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57