RF-DC101-K4

Trådlös dörr/fönsterkontakt, kan användas som universalsändare, vit 433 Mhz

In this series we are using KGS's 80+ wireless protocol in a 433Mhz frequency set-up, which allows for a better wireless indoor range. This 80+ protocol helps ensure security approvals.
This wireless door window sensor, which has 2 reed switches, protects anything that opens and closes such as doors, windows and cabinets. You can monitor any supervised contact in such a way that hardwired devices become wireless in a fraction of time.
The sensor is equipped with a wall and cover tamper for additional security.
This series comes in a white and a mahogany version and also has accessories in both colors.



Detaljer

- 80+ wireless protocol using 433Mhz for improved indoor range
- 5-years battery life
- Battery pull-tab concept
- Selectable reed switches
- Additional terminal block
- Range of accessories : two types of spacers and a stronger magnet
- Holding EN and Incert certificates

RF-DC101-K4

Trådlös dörr/fönsterkontakt, kan användas som universalsändare, vit 433 Mhz

Tekniska specifikationer

General

Application type	Ytmontering
Contact type	Reed switch

Wired/wireless

Wired-wireless	Trådløs
Wireless frequency	433 MHz LoNa
Open-air range	400 m

Electrical

Battery lifetime	>5 years with supervis. signal per 15 min. and 4 activations/hour

Physical

Colour	Hvid

Regulatory

EN50131 grade	Lønklasse 2

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57